

GDLM-3xxxxxx

**1.31um MQW-DFB Laser Diode pigtail Module:
Analog from 1GHz to 2GHz application**



Features

- ◆ Coaxial Package
- ◆ InGaAsP/InP MQW-DFB laser Diode
- ◆ Low threshold, high slope efficiency and high output power LD
- ◆ Operating case temperature: -40°C to +85°C
- ◆ Single-mode fiber pigtailed with SC, LC, FC or ST connector
- ◆ Optional with Isolator
- ◆ RoHS Compliant

Applications

- ◆ CATV Analog Return Path Optical Transmitter
- ◆ GSM/CDMA Optical Repeater
- ◆ W-CDMA/CDMA2000/TD-SCDMA Optical Repeater
- ◆ Microwave Transmission System
- ◆ Test Equipments

General

GDLM-3xxxxxx Series are 1.31µm InGaAsP/InP MQW-DFB laser diode modules designed for fiber optic communication systems. These modules are receptacle modules, and have low threshold current and high performance at high temperature.

A laser diode is mounted into a coaxial package integrated with a single mode fiber pigtail, an isolator and an InGaAs monitor PD.

Ordering information (Standard version ^{*Note1})

Part No.	Package series	Pin Type	Isolator	Connector	RF Bandwidth
GDLM-3010ASA1G	A	LD-Pin-1	Single Stage	SC/APC	<1GHz
GDLM-3120BFA2G	B	LD-Pin-2	Single Stage	FC/APC	<2GHz
GDLM-3120CSA1G	C	LD-Pin-1	Single Stage	SC/APC	<2GHz
GDLM-3020DT1G	D	LD-Pin-1	Single Stage	ST/PC	<1GHz
GDLM-3120EFA2G2	E	LD-Pin-2	Dual Stage	FC/APC	<2GHz
GDLM-3120CFA1G2	C	LD-Pin-1	Dual Stage	FC/APC	<2GHz

*Note1: For more ordering information, please refer the nomenclature and contact EPOTOLINK sales.

Absolute maximum ratings *Note2

Parameter	Symbol	Ratings	Unit
Storage temperature	Tstg	-40~+100	°C
Operating case temperature	Top	-40~+85	°C
Forward current (LD)	IfL	150	mA
Reverse voltage (LD)	VrL	2	V
Reverse voltage (PD)	VrP	15	V
Reverse current (PD)	IrP	2	mA
Soldering temperature (<10s)	Stemp	260	°C

*Note2: Exceeding any one of these values may destroy the device immediately.


Electrical and optical characteristics

(Po=3mW, SMF, Tc=+25°C, unless otherwise noted.)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Threshold current	Ith	CW	—	8	15	mA
		CW, Tc=-40~+85	—	—	40	
Output Power (After coupled)	Po	CW, If=Ith+20mA	1	2.5	3	mW
Operating current	If	CW	—	30	40	mA
		CW, Tc=-40~+85	—	40	70	
Operating voltage	Vf	CW, Tc=-40~+85	—	—	1.6	V
Slope efficiency	Se	CW	0.05	—	0.15	mW/mA
Wavelength	λ_c	CW	1290	1310	1325	nm
		CW, Tc=-40~+85	1280	—	1335	
Spectral Width	$\Delta\lambda$	CW, -20dB, Tc=-40~+85	—	—	1	nm
Side-mode suppression ratio	SMSR	CW, Tc=-40~+85	30	—	—	dB
Tracking error	ΔPf	Im hold(@Pf=3mW(25°C)), CW, TC=-40~+85	-1	—	1	dB
Relative intensity noise*Note3	RIN	CW	—	—	-145	dB/Hz
Monitor current	Im	CW, VrP=5V, Tc=-40~+85	80	300	—	uA
Monitor dark current	Id	CW, VrP=5V	—	1	10	nA
Monitor capacitance	C	Vrp=5V, f=1MHz	—	—	10	pF
Connector repeatability	—	—	-1	—	1	dB
Optical Isolation	—	Single Stage	30	—	—	dB
	—	Dual Stage	40	—	—	

*Note3: Zero link loss, f=1780MHz

Pigtail Package dimension *Note4· 5· 6




*Note4: PIN direction and laser mark can be customized. Pigtail is standard SM fiber; the length also can be customized.

*Note5: For the package series D, the clamping rings dimensions (A) and drill size (B) are can be selected. The following types can be available. Please designate the detailed type while ordering the package series D.

Fixed card type	A(mm)	B(mm)
D	16	12
D-S	17	12.7


*Note6: For the package series B, the fix card is fixed by customer self. For the detailed information of fix card of A, C, D package series, please refers the following graphs.

The direction of fix card




Pin Assignment

TYPE: 1



LD-pin-1 / TYPE: C

TYPE: 2



LD-pin-2 / TYPE: B

Nomenclature

G D L M —
 A B C D E F G

Order	Parameter	Detailed Description			
A	Center Wavelength	3=1310			
B	RF Bandwidth	0<1GHz		1<2.GHz	
C	Power	10=1-1.99mW		20=2-2.99mW	
D	Package series	A	B	C	D E
E	Connector	F=FC/PC	S=SC/PC	T=ST/PC	L=LC/PC
		FA=FC/APC	SA=SC/APC	LA=LC/APC	Blank=None
F	Pin Type	1=LD-pin-1		2=LD-pin-2	
G	Isolator	Blank=None		G= Single Stage	G2=Dual Stage

Nomenclature of assembly direction *Note7

Code: P LD X X - X
 Pigtail | Laser Diode | Assembly Direction
 1=Type-1
 2=Type-2
 A=A Type Fixed Cards
 C=C Type Fixed Cards
 D=D Type Fixed Cards

*Note7: Please designate the code of assembly direction.

Precaution

- (1) The modules should be handled in the same manner as ordinary semiconductor devices to prevent the electro-static damages. For safe keeping and carrying, the modules should be packaged with ESD proof material. To assemble the modules on PCB, the workbench, the soldering iron and the human body should be grounded.
- (2) Please pay special attention to the atmosphere condition because the dew on the module may cause some electrical damages.
- (3) Under such a strong vibration environment as in automobile, the performance and reliability are not guaranteed.

Obtaining Document

You can visit our website:

<http://www.eoptolink.com>

Or contact Eoptolink Technology Inc., Ltd. listed at the end of the documentation to get the latest documentation.

Revision History

Verision	Initiated	Reviewed	Approved	Release Date
Vb-1	Yinchun, Zhao	Kelly.Cao	Add the temp.Logo	2011-6-11
Vb-2	Jack.Jiang	Zore.Zhao	Delete power segments of information of "30"	2012-4-19
Vb-3	Jack.Jiang	Zore.Zhao Kelly.Cao	Add "RoHS Compliant"	2012-5-15

Notice:

Eoptolink reserves the right to make changes or discontinue any product or service identified in this publication, without notice, in order to improve design and/or performance. Applications that are described herein for any of the products are for illustrative purposes only. Eoptolink makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Contact:

Add: Floor 5, Building 2, No. 21 Gaopeng Avenue, High-Tech District, CHENGDU, SICHUAN 610041 P.R.

CHINA

Tel: (+86) 028-85122709 ext 816 & 809

Fax: (+86) 028-85121912

Postal: 610041

E-mail: sales@eoptolink.com

<http://www.eoptolink.com>

Eoptolink Technology Co., Ltd.