

PRODUCT DETAILS

Eoptolink's 800G Multi mode OSFP to QSFP-DD AOC



EOLO-8HG-PCT-XX-G Series

800G, OSFP to QSFP-DD

With AOC interface

Product Description

Eoptolink's OSFP 800G to QSFP-DD 800G AOC is designed for use in 800 Gigabit Ethernet links over 30m. Each end of the AOC module has 8 independent electrical input/output channels operating at 106.25Gbps per channel. Each end of the AOC module consists of two transmitter/receiver units. The transmitter path of the module incorporates a bi-directional PAM4 retimer ASIC integrated with two 4-channel drivers, 8 externally modulated laser. On the receiver path, 8 photodiodes and two 4-channel TIAs are used, along with a PAM4 retimer. The electrical interface of the module is compliant with the 800GAUI-8 interface defined by IEEE 802.3df and compliant with OSFP MSA and QSFP-DD MSA.

Features

- Supports 850Gbps
- Single 3.3V Power Supply
- Power Dissipation <15W (Each end)
- Up to 30m over MMF
- 8x53.125GBd (PAM4) Electrical Interface
- Case Temperature Range of 15°C to 70°C
- VCSEL Transmitter
- PIN and TIA on the Receiver Side
- I2C interface with Integrated Digital Diagnostic Monitoring
- OSFP MSA Compliant
- QSFP-DD MSA Compliant
- Safety Certification: TUV/UL/FDA*¹
- RoHS Compliant (Lead-free)

Applications

- 8x100G Ethernet
- 2x400G Ethernet
- 1x800G Ethernet
- 4x200G Ethernet

Ordering Information



Part No. ^{*2}	Data Rate	Fiber	Distance	Interface	Temp.	DDMI	CMIS
EOLO-8HG-PCT-XX-G	850Gbps	MMF	Up to 30m	AOC	15~70°C	Yes	CMIS5.0 ^{*3}

*1: For more details, please check with Eoptolink.

*2: XX=01, 03, 05, 07, 10, 15, 20, 30 denotes the AOC length with unit meter. For example, 01 denotes 1m, 03 denotes 3m ... 30 denotes 30m. Eight lengths above are the typical lengths which are suggested to choose.

*3: CMIS5.0 or later version.

Quality

Eoptolink Technology has passed many quality system verifications, established an internationally standardized quality assurance system and strictly implemented standardized management and control in the course of design, development, production, installation and service. For latest certification/accreditation numbers, please, contact us.



Notice

Eoptolink reserves the right to make changes or discontinue any optical link product or service identified in this publication, without notice, in order to improve design and/or performance. Applications that are described herein for any of the optical link products are for illustrative purposes only. Eoptolink makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Eoptolink Technology Inc., Ltd.

USA Add: 3191 Laurelview Court Fremont, CA 94538.

Thailand Add: 390/21 Moo 2, Khao Khan Song Sub-district, Sriracha District, Chonburi Province, Thailand, 20110.

China Add: No.127 West Wulian Street, Shuangliu District, Chengdu City 610213, P.R.China.

Email: sales@eoptolink.com

<http://www.eoptolink.com/>