

## PRODUCT DETAILS

Eoptolink's 8×100G FR OSFP Optical Transceiver



# EOLO-138HG-02-xDx

Single-Mode, 800G, 2×400G or 8×100G OSFP  
With Dual MPO-12 interface

## Product Description

Eoptolink's OSFP 8x100Gbps transceiver module can be used for 800 Gigabit Ethernet connections over 2km of single-mode fiber. The module includes eight parallel channels with a central wavelength of 1310nm, and the operating rate of each channel is 106.25Gbps. These 8-channel PAM4 parallel optical signals can be converted into 8-channel PAM4 electrical output signals; and there are 8 independent electrical input/output channels, which can convert PAM4 electrical input data into 8-channel PAM4 parallel optical signal. The transmitter of the module includes a bi-directional PAM4 re-timer ASIC with an 8-channel modulator driver and 8 EML Lasers. The receiver uses 8 photodiodes and integrated TIA, as well as the PAM4 re-timer. The electrical interface of the module is compliant with the 800GAUI-8 interface as defined by IEEE 802.3ck, and compliant with OSFP MSA.

## Features

- Supports 850Gbps
- Single 3.3V Power Supply
- Up to 2km over SMF with KP4 FEC supported at the Host side
- Dual MPO-12 connector
- 8x106.25Gbps (PAM4) electrical interface
- Driver and TIA integrated in the DSP at transmitter and receiver side
- Power dissipation < 14.5W
- Case temperature range: 0°C to 70°C (commercial)
- Safety Certification: TUV/UL/FDA\*1
- RoHS Compliant

## Applications\*1

- 8x100G Ethernet
- 2x400G Ethernet
- 1x800G Ethernet



## Ordering Information

Part No.	Data Rate	Fiber	Distance*2	Interface	Temp.	DDMI	CMIS
EOLO-138HG-02-xDx*1	850Gbps	SMF	2km	Dual MPO-12	0~70°C	Yes	CMIS5.0*3

\*1: For more details, please contact with Eoptolink.

\*2: Over G.652 SMF.

\*3: CMIS5.0 or later version.

## Quality

Eoptolink Technology has passed many quality system verifications, established an internationally standardized quality assurance system and strictly implemented standardized management and control in the course of design, development, production, installation and service. For latest certification/accreditation numbers, please, contact us.



## Notice

Eoptolink reserves the right to make changes or discontinue any optical link product or service identified in this publication, without notice, in order to improve design and/or performance. Applications that are described herein for any of the optical link products are for illustrative purposes only. Eoptolink makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

## Eoptolink Technology Inc., Ltd.

USA Add: 3191 Laurelview Court Fremont, CA 94538.

Thailand Add: 390/21 Moo 2, Khao Khan Song Sub-district, Sriracha District, Chonburi Province, Thailand, 20110.

China Add: No.127 West Wulian Street, Shuangliu District, Chengdu City 610213, P.R.China.

Email: [sales@eoptolink.com](mailto:sales@eoptolink.com)

<http://www.eoptolink.com/>